



UN 3480 (under UN Model Regulation)		UN 3481 (under UN Model Regulation)	
(NEW) Lithium-Ion Cells and Batteries		(NEW) Lithium-Ion Cells and Batteries Installed in or Packed with Equipment	
Not more than 100 Wh	Above 100 Wh	Not more than 100 Wh	Above 100 Wh
	FULLY REGULATED		FULLY REGULATED
Batteries tested under § 38.3 (UN Tests & Manual Criteria)	Batteries tested under § 38.3 (UN Tests & Manual Criteria)	Batteries tested under § 38.3 (UN Tests & Manual Criteria)	Batteries tested under § 38.3 (UN Tests & Manual Criteria)
Wh marking on battery	Wh marking on battery (starting 2011).	Wh marking on battery	Wh marking on battery (starting 2011).
Short Circuit Protection	CLASS 9, Packing Group II packaging, Class 9 Markings and Labelling, TRANSPORT CATEGORY 2, Tunnel Restriction code E	Short Circuit Protection	CLASS 9, Strong outer packaging when installed in equipment, Packing Group II packaging for batteries when packed with equipment; Class 9 Markings and Labelling, TRANSPORT CATEGORY 2, Tunnel Restriction code E
Individual separation of cells and batteries		When installed in equipment, package to prevent accidental activation. When packed with equipment, batteries shall be packed in inner packaging that completely enclose the battery.	
Strong Outer Packaging Marking on package to indicate presence of lithium batteries, package shall be handled with care and flammability hazard exists if package is damaged, special procedures should be followed in the event the package is damaged and telephone number for more additional information Accompanying document containing same information as marking (Delivery Note)		Strong Outer Packaging When more than 4 cells or 2 batteries installed in equipment or if batteries are packed with equipment, marking on package to indicate presence of lithium batteries, package shall be handled with care and flammability hazard exists if package is damaged, special procedures should be followed in the event the package is damaged and telephone number for more additional information When more than 4 cells or 2 batteries installed in equipment or if batteries are packed with equipment, accompanying document containing same information as marking (Delivery Note)	
Gross weight of package may not exceed 30 kg		No weight limit	
1.2 m drop test for package		1.2 m drop test for package of batteries packed with equipment or outer package.	

RECHARGE makes no representations or warranties as to the completeness, accuracy, adequacy, currency, or reliability of this information and shall not be liable for any lack of the foregoing. Furthermore, the information does not constitute legal advice on transportation regulations, and should not be considered legal advice, nor substitute for obtaining legal advice.